




Artira


Inclined Platform Lift For Straight And Turning Stairways

Technical Information


Configurations




Turning Multi-Stop Stairway




Access onto a Stage



Straight Stairway with Intermediate Horizontal Section



Straight Stairway with Platform Storage off the Stairs




Radiating Stairway

Specifications

| | |
|--------------------------|--|
| Load Capacity | 300 Kg (660 Lbs.) at up to 45° stair angle for public use |
| Power Requirements | 208-240 VAC, 50/60 Hz on a dedicated 20 amp circuit |
| Platform Sizes | 4 standard sizes including large ADA-compliant 800 mm x 1200 mm (31.5" x 48") platform. |
| Attachment | Mounted directly to a wall or attached to stair treads using support towers (requires sufficient substrate strength). |
| Controls | Smart-Lite Technology™ guides the user through operation by illuminating the appropriate button. Safety code requires continuous pressure on control buttons to operate the lift (keep button depressed to keep moving). Buttons are large and easy to use for everyone. |
| Platform Storage | Folded platform conceals and protects safety barrier arms and platform controls from vandalism. |
| Standard Finishes | Indoor units - RAL 7030 fine texture Satin Grey. Outdoor - bead blasted and electropolished stainless steel. Custom RAL colors available. |
| Standard Safety Features | Under-platform obstruction sensors, pedestrian safety lights, bi-directional ramp sensors, emergency manual folding and lowering, curved safety barrier arms, overspeed prevention system |
| Optional Features | Attendant remote control, under hanger sensors, side of hanger sensors, automatic platform fold, fold-down seat and seatbelt, building fire alarm integration, side load for confined lower landings, wall-mount pedestrian audio-visual alert, pedestrian handrails integrated in to support rail system. |

Dimensions

Turning Clearances



Platform Sizes

| Dim. | Attachment Method | 800 x 1220 mm (31 1/2" x 48") | | 800 x 1050 mm (31 1/2" x 41 3/8") | | 800 x 900 mm (31 1/2" x 35 3/8") | | 700 x 750 mm (27 1/2" x 29 1/2") | |
|----------|-------------------|----------------------------------|--------|--------------------------------------|--------|-------------------------------------|--------|-------------------------------------|--------|
| | | mm | in | mm | in | mm | in | mm | in |
| A | Direct Mount | 125 | 4 7/8 | 125 | 4 7/8 | 125 | 4 7/8 | 125 | 4 7/8 |
| | Tower Mount | 150 | 5 7/8 | 150 | 5 7/8 | 150 | 5 7/8 | 150 | 5 7/8 |
| B | Direct Mount | 320 | 12 5/8 | 320 | 12 5/8 | 320 | 12 5/8 | 330 | 13 |
| | Tower Mount | 345 | 13 5/8 | 345 | 13 5/8 | 345 | 13 5/8 | 355 | 14 |
| C | Direct Mount | 1015 | 40 | 1015 | 40 | 1015 | 40 | 900 | 35 3/8 |
| | Tower Mount | 1040 | 41 | 1040 | 41 | 1040 | 41 | 925 | 36 3/8 |
| D | Direct Mount | 1230 | 48 3/8 | 1230 | 48 3/8 | 1230 | 48 3/8 | 1115 | 44 |
| | Tower Mount | 1255 | 49 3/8 | 1255 | 49 3/8 | 1255 | 49 3/8 | 1140 | 45 |
| E | Direct Mount | 1035 | 40 3/4 | 1035 | 40 3/4 | 1035 | 40 3/4 | 920 | 36 1/4 |
| | Tower Mount | 1060 | 41 3/4 | 1060 | 41 3/4 | 1060 | 41 3/4 | 945 | 37 1/4 |
| F | Direct Mount | 1225 | 48 1/4 | 1185 | 46 5/8 | 1145 | 45 1/8 | 1025 | 40 3/8 |
| | Tower Mount | 1250 | 49 1/4 | 1210 | 47 5/8 | 1170 | 46 1/8 | 1050 | 41 3/8 |




Garaventa Lift

T 604 594 0422 · **T** 800 663 6556 (toll free North America)
E info@garaventalift.com · **I** www.garaventalift.com



Authorized Garaventa Lift Representative

© Garaventa Lift. As we are continuously improving our products, specifications outlined in this brochure are subject to change without notice.

 Printed in Canada
15814-M-PB